

# AUTOMOTIVE RELAY 1 POLE x 2 - 12A (28VDC) for 24V battery automotive applications

# FBR572, 582 Series

### **RoHS Compliant**

### FEATURES

- Two independent relays mounted in a single package
- High current contact capacity (carrying current: 40A/2 minutes, 30A/1 hour)
- Suitable for controlling 24V motors in trucks and other large vehicles
- High heat resistance and extended operating voltage
- Two types of contact gap (FBR572: 0.8 mm, FBR582: 1.4 mm)
- RoHS compliant



### APPLICATIONS

Body control (power window, door lock etc.)

### PART NUMBERS

[Example]	FBR572	<u>N</u>	<u>D24</u>	-	<u>W1</u>	**
	(a)	(b)	(c)		(d)	(e)

(a)	Relay type	FBR572 FBR582	: FBR572 series (contact gap 0.8mm) : FBR582 series (contact gap 1.4mm)
(b)	Enclosure	N	: Plastic sealed type
(c)	Coil rated voltage	D24	: 24VDC Please refer to coil rating table
(d)	Contact material	W1 Y	: Silver-tin oxide indium : Silver-tin oxide
(e)	Special type	To be ass	igned custom specification

Actual marking does not carry the type name: "FBR"

E.g.: Ordering code: FBR572ND24-W1 Actual marking: 572ND24-W1

### SPECIFICATIONS

Item		Specifications		Demerika/Conditione	
		FBR572	FBR582	Remarks/Conditions	
Contact	Configuration		1c (1 form C, SPDT) x 2		
Data	Meterial		Silver-tin oxide indium (-W1 type)		
	wateria		Silver-tin oxide (-Y type)		
	Voltage drop		Max. 1	100mV	Initial at 1A, 12VDC
	Contact rating		12A, 28VDC (locked motor load)		
	Contact rating		Inrush 15A, break 2.5A, 28VDC (motor free load)		
	Max. carrying cu	ırrent	40A / 2 minutes (at 25°C	, 100% rated coil voltage)	
	Max. inrush current		60	A	Reference
	Max. switching voltage		28VDC	32VDC	Reference
	Max. switching current		12A	14A	Reference
	Min. switching load <sup>*1</sup>		1A, 6VDC		Reference
Coil	Operating temperature range		-40°C to +85°C		No frost
	Storage temperature range		-40°C to +100°C		No frost
Time	ne Operate		Max. 10 ms		At nominal voltage
	Release		Max. 5 ms		At nominal voltage
Life	Mechanical		Min. 10 x 10 <sup>6</sup> operations	Min. 1 x 10 <sup>6</sup> operations	
	Electrical	Locked motor load	Min. 100 x 10 <sup>3</sup> operations	Min. 100 x 10 <sup>3</sup> operations	
	Liectifical	Motor free load	Min. 500 x 10 <sup>3</sup> operations	-	
Others		Misoperation	10 to 200Hz acceleration 44m/s <sup>2</sup> (4.5G),		Coil ON/OFF, 3 axis,
	Vibration		constant acceleration		total 6 cycles
	resistance	Endurance	10 to 200Hz acceleration 44m/s <sup>2</sup> (4.5G),		Coil OFF, 3 axis, total 6
		Endurance	constant acceleration		hours
	Misoperation	$100 \text{m/s}^2 (11+1 \text{ms})$		Coil ON/OFF, 3 axis,	
	Shock resistance		10011/3 (11±1113)		total 36 operations
		Endurance	1,000m/s² (6±1ms)		Coil OFF, 3 axis, total
					18 operations
Dimensions / Weight		20.0 x 26.0 x 16.2mm / Approx. 18g			

\*1: Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

Care shall be taken on the heat generated on PC board when maximum carrying current exceeds 10A. Please perform the confirmation test with actual conditions.

### COIL DATA

Series	Coil Code	Rated Coil Voltage (VDC)	Coil Resistance ±10% (Ω)	Must Operate Voltage <sup>*1</sup> (VDC)	Must Release Voltage <sup>*1</sup> (VDC)
FBR572 D24	24	384	14.4 (at 20°C)	1.9 (at 20°C)	
		304	18.0 (at 85°C)	2.4 (at 85°C)	
FBR582 D24	24	170	14.4 (at 20°C)	2.0 (at 20°C)	
	DZ4	24	170	18.0 (at 85°C)	2.6 (at 85°C)

Note: All values in the table are valid for 20°C and zero contact current unless otherwise specified.

\*1: Specified operated values are valid for pulse voltage.

Please use at rated coil voltage. Please refer to characteristic data and set up adequate voltage in case of use at over voltage.

### PART NUMBER LIST

Part Number	Contact Gap	Enclosure	Contact Material	Contact Arrangement	
FBR572ND24-W1	0.9mm	Directio accolord	Silver-tin oxide indium		
FBR572ND24-Y	0.0000	Plastic sealed	Silver-tin oxide	$10(1 \text{ Form } C \text{ SPDT}) \times 2$	
FBR582ND24-W1	1.4mm	Directio accolord	Silver-tin oxide indium		
FBR582ND24-Y	1.4mm	Plastic sealed	Silver-tin oxide		

### DIMENSIONS



### ■ CHARACTERISTIC DATA

(Characteristic data is not guaranteed value but measured values of samples from production line.)





#### Life Test

(1) Motor lock



#### (2) Motor free

Test Item	Test Circuit	Current Wave Form	
Inrush 15A, Break 2.5A 28VDC Motor free 500,000 operations minimum Contact material: Silver tin oxide indium	N.O. N.C	15 A 0 A	

### CHARACTERISTIC DATA

(Characteristic data is not guaranteed value but measured values of samples from production line.)





Detection level: chatter > 1ms



#### CHARACTERISTIC DATA

(Characteristic data is not guaranteed value but measured values of samples from production line.)



Nominal voltage multiplying factor (%)

## CAUTIONS

- All values mentioned in this datasheet are provided under ideal conditions. Please perform the confirmation test before actual use.
- Reflow soldering is prohibited.
- Do not use relays in the atmosphere with sulfide gas, chloride gas or nitric oxide. Contact resistance may increase.
- · Do not use silicon or silicon-containing product or materials near relays. It may cause contact failure.

### **GENERAL INFORMATION**

### 1. ROHS Compliance

• All relays produced by FCL Components are compliant with RoHS directive 2011/65/EU, including commission delegated directive 2015/863.

### 2. Recommended lead free solder condition

- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.
- Recommended solder for assembly: Sn-3.0Ag-0.5Cu.

### Flow Solder Condition:

Pre-Heating: Maximum 120°C within 90 sec.

Soldering: Dip within 5 sec. at 255°C±5°C solder bath

Relay must be cooled by air immediately after soldering

### Solder by Soldering Iron:

Soldering Iron:30-60WTemperature:Maximum 340-360°CDuration:Maximum 3 sec.

### We highly recommend that you confirm your actual solder conditions

### 3. Moisture Sensitivity

• Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

• Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

### Contact

#### Japan

FCL COMPONENTS LIMITED Shinagawa Seaside Park Tower 12-4, Higashi-shinagawa 4-chome, Tokyo 140 0002, Japan Tel: +81-3-3450-1682 Email: fcl-contact@cs.fcl-components.com

#### Asia Pacific

FCL COMPONENTS ASIA PTE LTD. 51 Changi Business Park Central 2, #06-07 The Signature Singapore 486066 Tel: +65-6375-8560 Email: fcal@fcl-components.com

#### North and South America

FCL COMPONENTS AMERICA, INC. 2055 Gateway Place Suite 480, San Jose, CA 95110 USA Tel: +1-408-745-4900 Email: contact@fcl-components.us

#### China

FCL COMPONENTS (SHANGHAI) CO.,LTD. Unit 1105, Central Park - Jing An, No.329 Heng Feng Road, Shanghai 200070, China Tel: +86-21-3253 0998 Email: fcsh@fcl-components.com

#### Europe

FCL COMPONENTS EUROPE B.V. Diamantlaan 25 2132 WV Hoofddorp, Netherlands Tel: +31-23-556-0910 Email: info@fcl-components.eu

#### Hong Kong

FCL COMPONENTS HONG KONG CO., LIMITED Unit 2313, Seapower Tower, Concordia Plaza, No.1 Science Museum Road, TST, Kowloon, Hong Kong Tel: +852-2881-8495 Email: fcal@fcl-components.com

Web: www.fcl-components.com/en/

© 2025 FCL Components Limited. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

FCL Components Products are intended for general use, including without limitation, in personal, household and office environments, in buildings and for ordinary use in the industry. FCL Components Products are not intended to be used in applications where extremely high safety is required ("High Safety Required Applications"), such as, but not limited to, applications in nuclear facilities, in aircraft automatic flight control, in air traffic control, in mass transit system control, in missile launch system, in weapon systems, in medical equipment for life support or any application involving a direct serious risk of physical injury or death.

Please do not use FCL Components Products without securing the sufficient safety and reliability required for the High Safety Required Applications.

In addition, FCL Components shall not be liable against the customer and/or any third party for any claims or damages arising in connection with the use of FCL Components Products in the High Safety Required Applications.

FCL Components warrants that its Products, if properly used and services, will conform to their specification and will be free from defects in material and workmanship for twelve months from delivery.

The implied warranties of merchantability and fitness for a particular purpose and all other warranties, representations and conditions, express or implied by statute, trade usage or otherwise, expect as set forth in this warranty, are excluded and shall not apply to the Products delivered.

The contents, data and information in this datasheet are provided by FCL Components Limited as a service only to its user and only for general information purposes. The use of the contents, data and information provided in this datasheet is at the users' own risk.

FCL Components has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

FCL Components Limited and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Nor do FCL Components Limited and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability, accuracy, comprehensiveness, usefulness, availability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. April 3, 2025.