

COMPACT POWER RELAY

1 POLE - 25A (For Automotive Applications)

FTR-G1 Series

■ FEATURES

- Compact for high density packaging
- High contact capacity with proven contact material (min. 100,000 operations, 14V, 25A)
- Coil power savings (640mW nominal achieved with state-of-the-art magnetic analysis/design)
- Ease of PCB layout (all terminals on perimeter, coil and contact terminals separated)
- Lower noise (60dB average at 5cm)
- Plastic sealed
- Through hole reflow capable type available
- RoHS compliant

Please see page 6 for more information



■ APPLICATIONS

- Power window
- Door lock
- Tilt steering
- Sunroof
- Power seat
- Wiper/IWW
- Retractable antenna

■ PARTNUMBER INFORMATION

[Example] FTR-G1 C N 012 W1 - RW
 (a) (b) (c) (d) (e) (f)

(a)	Relay type	FTR-G1 : FTR-G1 Series
(b)	Contact configuration	C : 1 form C
(c)	Contact gap	N : 0.25 mm
(d)	Coil rated voltage	010 : 9.....12 VDC Coil rating table at page 3
(e)	Contact material / TV type	W1 : Silver-tin oxide indium
(f)	Soldering	Nil : Standard (Flow soldering) : Reflow capable (THR) RW

Actual marking does not carry the type name: "FTR"

E.g.: Ordering code: FTR-G1CN010W1 Actual marking: G1CN010W1

FTR-G1 SERIES

■ SPECIFICATION

Item	FTR-G1		
	Standard		Reflow capable
Contact Data	Configuration		1 form C
	Material		Silver-tin oxide indium
	Contact voltage drop		Max. 100mV at 1A, 6VDC (after stabilization)
	Contact rating		25A at 14VDC (locked motor load)
	Max. carrying current * ¹		25A/1 hour (25 °C, 100% rated coil voltage)
	Max. switching voltage		16VDC (reference)
	Max. switching current		35A (reference)
	Min. switching load * ²		1A, 6VDC
Life	Mechanical		Min. 10 x 10 ⁶ operations
	Electrical		* Min. 100 x 10 ³ operations, 14VDC, 25A inrush power window motor * Min. 100 x 10 ³ operations 14VDC, 20A inrush door locked motor
Coil Data	Rated power		640mW
	Operate power		237mW
	Operating temperature range		-40 °C to +85 °C (no frost) -40 °C to +125 °C (no frost)
Timing Data	Operate (at nominal voltage)		Max. 10 ms (without bounce)
	Release (at nominal voltage)		Max. 5 ms (without bounce)
Insulation	Resistance (initial)		Min. 100MΩ at 500VDC
	Dielectric withstanding voltage	Open contacts	500VAC, 1 min.
		Between coil and contacts	500VAC, 1 min.
Other	Vibration resistance	Misoperation	10 to 200Hz, 44m/s ² (4.5G), constant acceleration
		Endurance	10 to 200Hz, 44m/s ² (4.5G), constant acceleration
	Shock	Misoperation	100m/s ² minimum (11+/-1ms)
		Endurance	1,000m/s ² minimum (6+/-1ms)
	Weight		Approximately 3.5 g
	Sealing		Plastic sealed cat III

* 1 Care shall be taken on the heat generated on PC board when maximum carrying current exceeds 10A. Please perform the confirmation test with actual conditions.

* 2 Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

FTR-G1 SERIES

■ COIL RATING

Standard type

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance +/- 10% (Ohm)	Must Operate Voltage (VDC) *	Must Release Voltage (VDC) *
009	9	126	5.4	0.7
			6.8 (at 85 °C)	0.9 (at 85 °C)
010	10	160	6.5	0.8
			8.2 (at 85 °C)	1.0 (at 85 °C)
012	12	225	7.3	1.0
			9.2 (at 85 °C)	1.3 (at 85 °C)

Reflow capable type

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance +/- 10% (Ohm)	Must Operate Voltage (VDC) *	Must Release Voltage (VDC) *
009	9	126	5.4	0.7
			6.8 (at 85 °C)	0.9 (at 85 °C)
			7.6 (at 125 °C)	1.0 (at 125 °C)
010	10	160	6.5	0.8
			8.2 (at 85 °C)	1.0 (at 85 °C)
			9.2 (at 125 °C)	1.1 (at 125 °C)
012	12	225	7.3	1.0
			9.2 (at 85 °C)	1.3 (at 85 °C)
			10.3 (at 125 °C)	1.4 (at 125 °C)

Note: All values in the table are valid for 20 °C and zero contact current, unless otherwise indicated.


* Specified operate values are valid for pulse wave voltage.

FTR-G1 SERIES


CHARACTERISTIC DATA

(Characteristic data is not guaranteed value but measured values of samples from production line.)


Distribution of operate/release voltage




Distribution of contact resistance




Contact current




Ambient temperature vs voltage (standard type)




Ambient temperature vs voltage (reflow capable type)




Coil temperature rise




Coil temperature rise



Vibration resistance






Shock resistance






FTR-G1 SERIES

■ DIMENSIONS


● Dimensions (Standard type)




● Dimensions (Reflow capable type)



● Schematics (BOTTOM VIEW)



● PC board mounting hole layout (BOTTOM VIEW)



- * Dimensions of the terminals do not include thickness of pre-solder.
- * Tolerance of PC board mounting hole layout : ± 0.1 unless otherwise specified.
- * Dimensions do not include tolerances. Please ask specification in case you need tolerances.

(1) :
Reference
Unit: mm

CAUTIONS

- All values mentioned in this datasheet are provided under ideal conditions. Please perform the confirmation test before actual use.
- Reflow soldering is prohibited for flow soldering type.
- Do not use relays in the atmosphere with sulfide gas, chloride gas or nitric oxide. Contact resistance may increase.
- Do not use silicon or silicon-containing product or materials near relays. It may cause contact failure.

GENERAL INFORMATION

1. ROHS Compliance

- All relays produced by FCL Components are compliant with RoHS directive 2011/65/EU, including commission delegated directive 2015/863.

2. Recommended lead free solder condition

- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.
- Recommended solder for assembly: Sn-3.0Ag-0.5Cu.

Flow Solder Condition:

Pre-Heating: maximum 120°C
within 90 sec.
Soldering: dip within 5 sec. at 255°C±5°C
solder bath

Relay must be cooled by air immediately after soldering


Solder by Soldering Iron:

Soldering Iron: 30-60W
Temperature: maximum 350-360°C
Duration: maximum 3 sec.

Reflow Solder Condition:

(Applicable only for reflow capable type)

Recommended reflow soldering profile:
IRS (infrared reflow soldering)



Important Notes for reflow Soldering

- Temperature shall be measured at PC board upper surface.
- Temperature at PC board upper surface may be changed depending on size of PC board, components mounted on the PC board and/or heating method. Please perform the confirmation test with your actual PC board.
- This reflow condition is applicable only for reflow-capable relays. Do not reflow reflow-incapable relays.

We highly recommend that you confirm your actual solder conditions

3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

Contact

Japan

FCL COMPONENTS LIMITED
Shinagawa Seaside Park Tower
12-4, Higashi-shinagawa 4-chome,
Tokyo 140 0002, Japan
Tel: +81-3-3450-1682
Email: fcl-contact@cs.fcl-components.com

North and South America

FCL COMPONENTS AMERICA, INC.
2055 Gateway Place Suite 480,
San Jose, CA 95110 USA
Tel: +1-408-745-4900
Email: fcai.components@fcl-components.com

Europe

FCL COMPONENTS EUROPE B.V.
Diamantlaan 25
2132 WV Hoofddorp, Netherlands
Tel: +31-23-556-0910
Email: info.fceu@cs.fcl-components.com

Asia Pacific

FCL COMPONENTS ASIA PTE LTD.
No. 20 Harbour Drive, #07-01B
Singapore 117612
Tel: +65-6375-8560
Email: fcal@fcl-components.com

China

FCL COMPONENTS (SHANGHAI) CO., LTD.
Unit 1105, Central Park - Jing An,
No.329 Heng Feng Road, Shanghai 200070,
China
Tel: +86-21-3253 0998
Email: fcsh@fcl-components.com

Web: www.fcl-components.com/en/

© 2024 FCL Components Limited. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

FCL Products are intended for general use, including without limitation, in personal, household and office environments, in buildings and for ordinary use in the industry. FCL Products are not intended to be used in applications where extremely high safety is required ("High Safety Required Applications"), such as, but not limited to, applications in nuclear facilities, in aircraft automatic flight control, in air traffic control, in mass transit system control, in missile launch system, in weapon systems, in medical equipment for life support or any application involving a direct serious risk of physical injury or death.

Please do not use FCL Products without securing the sufficient safety and reliability required for the High Safety Required Applications. In addition, FCL shall not be liable against the customer and/or any third party for any claims or damages arising in connection with the use of FCL Products in the High Safety Required Applications.

FCL warrants that its Products, if properly used and services, will conform to their specification and will be free from defects in material and workmanship for twelve months from delivery.

The implied warranties of merchantability and fitness for a particular purpose and all other warranties, representations and conditions, express or implied by statute, trade usage or otherwise, except as set forth in this warranty, are excluded and shall not apply to the Products delivered.

The contents, data and information in this datasheet are provided by FCL Components Limited as a service only to its user and only for general information purposes. The use of the contents, data and information provided in this datasheet is at the users' own risk.

FCL has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

FCL Components Limited and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof.

Nor do FCL Components Limited and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. February 1, 2024.
