

# POWER RELAY


## 1 POLE - 16A, 105°C SEALED TYPE

### FTR-K1 Series

RoHS Compliant

#### ■ FEATURES

- 1 pole
- 16A
- 1 form A / 1 form C
- Coil sensitive 400mW
- High insulation in small package (between coil and contacts)
  - Insulation distance: 10mm min.
  - Dielectric strength: 5,000VAC
  - Surge strength: 10,000V
- UL F class insulation wire
- Cadmium free contacts
- Plastic sealed type, RTIII
- RoHS compliant



#### ■ APPLICATIONS

Heater control, microwave toaster oven combo, cooking table etc.

#### ■ PART NUMBERS

[Example] FTR-K1   C   K   012   W   -   KW  
                   (a)       (b)   (c)   (d)   (e)       (f)

(a)	Relay type	FTR-K1 series
(b)	Contact configuration	A : 1a (1 Form A, SPST-NO) C : 1c (1 Form C, SPDT)
(c)	Coil type	K : Standard type (400mW)
(d)	Coil rated voltage	012 : 5...60VDC Please refer to coil rating table
(e)	Contact material	W : AgSnO <sub>2</sub>
(f)	Special type	KW : 105°C, plastic sealed type, RTIII

Actual marking does not carry the type name : "FTR"

E.g.: Ordering code: FTR-K1CK005W-KW Actual marking: K1CK005W-KW

## ■ SPECIFICATIONS

Item			Specifications		Remarks/Conditions
			FTR-K1AK( )W-KW	FTR-K1CK( )W-KW	
Contact Data	Configuration		1a (1 Form A)	1c (1 Form C)	
	Construction		Single		
	Material		AgSnO <sub>2</sub>		
	Resistance		Max. 100mΩ		Initial at 1A, 6VDC
	Contact rating		16A, 250VAC		Resistive
	Max. carrying current <sup>*1</sup>		20A		
	Max. switching voltage		440VAC		
	Max. switching power		4,000VA		
	Min. switching load <sup>*2</sup>		100mA, 5VDC		
Coil	Rated power (20°C)		400 to 430mW		
	Operate power (20°C)		200 to 210mW		
	Operating temperature range		-40°C to +105°C		No frost
Time	Operate		Max. 15ms		Without bounce, no diode
	Release		Max. 5ms		Without bounce, no diode
Life	Mechanical		Min. 20 x 10 <sup>6</sup> operations		
	Electrical		Min. 20 x 10 <sup>3</sup> ops.	Min. 10 x 10 <sup>3</sup> ops.	Rating resistive load
Insulation	Insulation resistance		Min. 1,000MΩ		At 500VDC
	Dielectric withstanding strength	Open contacts	1,000VAC (50/60Hz), 1 minute		
		Coil to contacts	5,000VAC (50/60Hz), 1 minute		
	Surge strength	Coil to contacts	10,000V / 1.2 x 50μs standard wave		
	Clearance / creepage		10mm / 10mm		
	EN61810-1, VDE0435	Voltage	250V		
		Pollution degree	3		
		Material group	IIIa		
		Category	C / 250		
Others	Vibration resistance	Misoperation≥1μs	10 to 55 to 10Hz single amplitude 0.35mm		Coil ON/OFF, 3 axis, total 6 cycles
		Endurance	10 to 55 to 10Hz single amplitude 0.75mm		Coil OFF, 3 axis, total 6 hours
	Shock resistance	Misoperation≥1μs	Min. 100m/s <sup>2</sup> (11±1ms)		Coil ON/OFF, 3 axis, total 36 operations
		Endurance	Min. 1,000m/s <sup>2</sup> (6±1ms)		Coil OFF, 3 axis, total 18 operations
	Dimensions / Weight		12.7 x 29.0 x 15.7 mm / approx. 13g		
	Sealing		Plastic sealed, RTIII		

\*1: Need to consider the heat from PCB when max. current is more than 10A.

\*2: Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels .

## ■ COIL DATA

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance $\pm 10\%$ ( $\Omega$ )	Must Operate Voltage <sup>*1</sup> (VDC)	Must Release Voltage <sup>*1</sup> (VDC)	Nominal Power (mW)
005	5	62	3.5	0.5	400
006	6	90	4.2	0.6	
009	9	202	6.3	0.9	
012	12	360	8.4	1.2	
018	18	810	12.6	1.8	
022	22	1,210	15.4	2.2	
024	24	1,440	16.8	2.4	
028	28	1,960	19.6	2.8	
048	48	5,360	33.6	4.8	430
060	60	8,570	42.0	6.0	420
110 <sup>*2</sup>	110 <sup>*2</sup>	28,800	77.0	11.0	

Note: All values in the table are valid for 20°C and zero contact current unless otherwise specified.

\*1: Specified operated values are valid for pulse voltage.

\*2: 110V coil is not for new design.

Note: Please use at rated coil voltage. Please refer to characteristic data and set up adequate voltage in case of use at over voltage.

## ■ SAFETY STANDARDS

Type	Compliance	Contact Rating	
		1a	1c
UL	Flammability: UL 94-V-0 (plastics)		
	UL508 File No. E63614	16A, 277VAC (resistive) 105°C 20A, 277VAC (resistive) 105°C	16A, 277VAC (resistive) 105°C
CSA	C22.2 No.14 LR40304	16A, 277VAC (resistive)	
VDE	EN60730-1 clause 12.2; 13.2; 20.1; 20.2; 20.3, EN60335-1 clause 15.3; 16.3; 29.1; 29.2; 29.3	16A, 250VAC ( $\cos\phi=1$ ), 105°C 20A, 250VAC ( $\cos\phi=1$ ), 105°C	16A, 250VAC ( $\cos\phi=1$ ), 105°C


## ■ PART NUMBER LIST

Part Number	Contact Configuration	Nominal Power	Contact Material
FTR-K1AK( )W-KW	1a (1 Form A)	Standard (Approx. 400 to 430mW)	AgSnO <sub>2</sub>
FTR-K1CK( )W-KW	1c (1 Form C)	Standard (Approx. 400 to 430mW)	AgSnO <sub>2</sub>


## ■ DIMENSIONS

### FTR-K1 -KW dimensions


#### Dimensions (FTR-K1AK( )W-KW)



#### Dimensions (FTR-K1CK( )W-KW)




#### Schematics (BOTTOM VIEW) (FTR-K1AK( )W-KW)




Connect terminal #1 and #8 on the PC board

#### Schematics (BOTTOM VIEW) (FTR-K1CK( )W-KW)




Connect terminal #1 and #8 on the PC board

#### PC board mounting hole layout (BOTTOM VIEW) (FTR-K1AK( )W-KW)



#### PC board mounting hole layout (BOTTOM VIEW) (FTR-K1CK( )W-KW)








- \* Dimensions of the terminals do not include thickness of pre-soldering.
- \* Tolerance of PC board mounting hole layout :  $\pm 0.1$  unless otherwise specified.
- \* Dimensions do not include tolerances. Please ask specification in case you need tolerances.


(Unit: mm)

## ■ CHARACTERISTIC DATA


(Characteristic data is not guaranteed value but measured values of samples from production line.)




Distribution of operate, release voltage



Distribution of operate, release time



Distribution of contact resistance



## CAUTIONS

- All values mentioned in this datasheet are provided under ideal conditions. Please perform the confirmation test before actual use.
- Reflow soldering is prohibited.
- Do not use relays in the atmosphere with sulfide gas, chloride gas or nitric oxide. Contact resistance may increase.
- Do not use silicon or silicon-containing product or materials near relays. It may cause contact failure.

## GENERAL INFORMATION

### 1. ROHS Compliance

- All relays produced by FCL Components are compliant with RoHS directive 2011/65/EU, including commission delegated directive 2015/863.

### 2. Recommended lead free solder condition

- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.
- Recommended solder for assembly: Sn-3.0Ag-0.5Cu.

#### Flow Solder Condition:

Pre-Heating: Maximum 120°C within 90 sec.

Soldering: Dip within 5 sec. at 255°C±5°C solder bath

Relay must be cooled by air immediately after soldering

#### Solder by Soldering Iron:

Soldering Iron: 30-60W

Temperature: Maximum 340-360°C

Duration: Maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

## Contact

### Japan

FCL COMPONENTS LIMITED  
Shinagawa Seaside Park Tower  
12-4, Higashi-shinagawa 4-chome,  
Tokyo 140 0002, Japan  
Tel: +81-3-3450-1682  
Email: [fcl-contact@cs.fcl-components.com](mailto:fcl-contact@cs.fcl-components.com)

### North and South America

FCL COMPONENTS AMERICA, INC.  
2055 Gateway Place Suite 480,  
San Jose, CA 95110 USA  
Tel: +1-408-745-4900  
Email: [contact@fcl-components.us](mailto:contact@fcl-components.us)

### Europe

FCL COMPONENTS EUROPE B.V.  
Diamantlaan 25  
2132 WV Hoofddorp, Netherlands  
Tel: +31-23-556-0910  
Email: [info@fcl-components.eu](mailto:info@fcl-components.eu)

### Asia Pacific

FCL COMPONENTS ASIA PTE LTD.  
No. 20 Harbour Drive, #07-01B  
Singapore 117612  
Tel: +65-6375-8560  
Email: [fcsl@fcl-components.com](mailto:fcsl@fcl-components.com)

### China

FCL COMPONENTS (SHANGHAI) CO.,LTD.  
Unit 1105, Central Park - Jing An,  
No.329 Heng Feng Road, Shanghai  
200070, China  
Tel: +86-21-3253 0998  
Email: [fcsh@fcl-components.com](mailto:fcsh@fcl-components.com)

### Hong Kong

FCL COMPONENTS HONG KONG CO.,  
LIMITED  
Unit 2313, Seapower Tower, Concordia  
Plaza, No.1 Science Museum Road,  
TST, Kowloon, Hong Kong  
Tel: +852-2881-8495  
Email: [fcsl@fcl-components.com](mailto:fcsl@fcl-components.com)

Web: [www.fcl-components.com/en/](http://www.fcl-components.com/en/)

© 2025 FCL Components Limited. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

FCL Components Products are intended for general use, including without limitation, in personal, household and office environments, in buildings and for ordinary use in the industry. FCL Components Products are not intended to be used in applications where extremely high safety is required ("High Safety Required Applications"), such as, but not limited to, applications in nuclear facilities, in aircraft automatic flight control, in air traffic control, in mass transit system control, in missile launch system, in weapon systems, in medical equipment for life support or any application involving a direct serious risk of physical injury or death.

Please do not use FCL Components Products without securing the sufficient safety and reliability required for the High Safety Required Applications.

In addition, FCL Components shall not be liable against the customer and/or any third party for any claims or damages arising in connection with the use of FCL Components Products in the High Safety Required Applications.

FCL Components warrants that its Products, if properly used and services, will conform to their specification and will be free from defects in material and workmanship for twelve months from delivery.

The implied warranties of merchantability and fitness for a particular purpose and all other warranties, representations and conditions, express or implied by statute, trade usage or otherwise, except as set forth in this warranty, are excluded and shall not apply to the Products delivered.

The contents, data and information in this datasheet are provided by FCL Components Limited as a service only to its user and only for general information purposes. The use of the contents, data and information provided in this datasheet is at the users' own risk.

FCL Components has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

FCL Components Limited and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Nor do FCL Components Limited and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. January 20, 2025