FUJITSU Thermal Printer

FUJITSU FP-2000C series



- ■1 Station Thermal POS Printer
- ■Ultra high speed, 400mm/sec
- ■Multi-function & Compact Design
- ■FUJITSU Super Green Product
- ■FUJITSU advanced printing algorithm
 - Dual printing mode, 180dpi & 203dpi
 - · New compression printing mode
 - FP-2200C 400mm/sec.
 - FP-2100C 300mm/sec.
 - FP-2000C 230mm/sec.

Specifications

| Model | | FP-2200C | FP-2100C | FP-2000C |
|---|---------------------------------|---|--------------------|------------------------------|
| Printing Technology | | Direct Line Ther | mal Method | |
| Print Resolution | | 8 dot/mm (0.125mm/dot), 203dpi | | |
| Print Speed (Monochrome only) | | Max. 400mm/s 360mm/sec: 50mm, 58mm width paper | Maximum 300mm/s | Maximum 230mm/s |
| Paper Feed-out Direction | | Top feed out | | |
| Cutter Method | | Full/Partial cut Partial cut | | |
| Installation Direction | | Two ways (Horizontal, Vertical) (LAN or RS232C+LAN card is inserted, Horizontal setting may not be available depending on the connector) | | |
| Paper | Paper width | 80mm, 58mm, 50mm | | |
| | Outer Diameter of Roll Paper | less than $ \phi $ 83mm | | |
| | Paper Thickness | 53µm - 85µm (53µm-65µm thickness paper with 50mm and 58mm width are not supported, but it is possible to print these thickness with paper guide) | | |
| Maximum Print Width | 50mm with paper | 45mm (360dots) | | |
| | 58mm with paper | 48mm (384dots) or 52.5mm (420dots) | | |
| | 80mm with paper | 64mm (512dots) or 72mm (576dots) | | |
| Barcode | Barcode | UPC-A, UPC-E, JAN13 (EAN13), JAN8(EAN8), CODE39, ITF, CODABAR(NW-7), CODE93, CODE128 | | |
| | Two dimensional code | QR code(Common to all models), PDF417 & DataMatrix(FP-2200&FP-2100) | | |
| Receive Buffer | | Max. 64 KB | | |
| Logo Store Memory | | 1088KB | | 576KB |
| Removing paper curl adjustment function | | Available | Not Available | Not Available |
| Paper Near End Sensor | | Available | | |
| Internal Buzzer | | Available to notice errors and printer status | | |
| Software Interface | | ESC/POS emulation | | |
| Drawer Interface | | 2 Drawers Controllable | | |
| RELIABILITY | MCBF | 70million Lines 60million Lines | | 60million Lines |
| | MTBF | Main Board : 360,000H | | |
| | Printer Mechanism life | 25 million line-feed 20 million line-feed | | 20 million line-feed |
| | Print Head | 150km 150million pulse | | 100km 100million pulse |
| | Cutter Life | 3million (Full cut: 2million) | 2million | 1.5million |
| Dimensions | | 128(W)x170(D)x126(H)mm, 5.0(W)x6.8(D) x4.9(H) inch | | |
| Weight (without the packing box) | | 1.0kg | | |
| Cover Color | | Ocean Black & Royal White | | |